

INSTALLATION MANUAL

6304




DC 45W 6
MOTOR MOTOR SPEED
WINTER REVERSE MOTOR
REMOTE CONTROL
LIGHT ON/OFF SWITCH
22W LED 2000 LUMEN

230V | LED 22W | DC MOTOR 45W | IP20 | Metal body | ABS blades | Rod mounted

· Maximum air flow rate 170m³/min
· Service value 3,7/W
· Standby power consumption 0,5W

· Fan sound power level 50dB(A)
· Maximum air velocity 4,0 m/sec.
· Max RPM 165



1 Install the fan blades and tighten screws.	2 Install LED plate and connect cable.	3 Install ceiling bracket.
4 Remove the R clip from the pin. Then remove the pin from the rod.	5 A Place the parts on the rod. B Pass wires through rod.	6 A Put the rod into the motor and install the pin and R clip. B Tighten all the nuts and screws.
7 A Hang the fan onto the ceiling bracket. B Lock into place.		8 Place the receiver on the hanger bracket.

Warnings:

1. Make sure that the product is installed properly before connecting to electricity.
2. Maintenance and installation should only be carried out by a professional electrician.

6304



1. Make sure that the product is installed properly before connecting to electricity.
2. Maintenance and installation should only be carried out by a professional electrician.

www.1-light.eu