



19 Garden & Underwater>The LED Bollards Range Cone reflector

67410A/AN/W



20W LED Bollard, IP65 for Garden illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	19 Garden & Underwater
Family	The LED Bollards Range Cone reflector
Order Code	67410A/AN/W
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	1000mm
Diameter	160mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

IK Rating	8
-----------	---

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	40V
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Osram

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	13,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Protection	Short Circuit

Illumination Data

Colour Temperature	3000K
Lumen Output	1600lm
Light Efficiency	80lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	5.900kg
Pcs/Carton	2
Barcode	5291889057482
HS Code	9405413990

Certification & Warranty

Warranty

2 years

Weee Directive

Yes

switch to
one light!

one
LIGHT

