

19 Garden & Underwater>Corridor Bollards

67494A/AN/W



3W Bollard with 2x1000W Schuko Sockets , IP44.

Complete with 350mA driver


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	19 Garden & Underwater
Family	Corridor Bollards
Order Code	67494A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Circular
Height	490mm
Diameter	100mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	5

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	8V
Power(Watts)	2,8W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 3014
LED Brand	Philips

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2,1-4,2W
Power Factor	0,9

Constant Current
350mA
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes
6-12V
IP20

No
Plastic
KGP

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram

3000K
240lm
80lm/W
80


Packing Info

Box Weight
Pcs/Carton
Barcode
HS Code

2.075kg
4
5291889067092
9405413990

Certification & Warranty

Warranty

2 years

switch to
one light!

