



19 Garden & Underwater>The Cage Light Bollards Aluminium

67506/AN/C



22W LED Bollard, IP65 for Garden illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	19 Garden & Underwater
Family	The Cage Light Bollards Aluminium
Order Code	67506/AN/C
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	160mm
Width	160mm
Height	600mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

IK Rating

10

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

22W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

39,31V

Power(Watts)

19,66W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Edison

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)	13,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	HEP
Protection	Short Circuit

Illumination Data

Colour Temperature	4000K
Lumen Output	1900lm
Light Efficiency	86,36lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	5.800kg
Pcs/Carton	1
Barcode	5291889069270
HS Code	9405413990

Certification & Warranty

switch to
one light!

