



20 Industrial & Floodlights>The LED Park Light CCT V

70112/B/V



CCT & Power Variable LED outdoor light for poles 3m and higher. Ideal for parks, parkings, playgrounds. Post Diameter 60mm.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery



Physical Specification

Item Group	20 Industrial & Floodlights
Family	The LED Park Light CCT V
Order Code	70112/B/V
Colour	Black
Material	Die Cast
Shape	Circular
Height	530mm



Diameter	450mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	120-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W-40W-60W-75W
IP Rating	IP66
Light Source	LED built in
Dimmable	No
Cable Length	150cm
F Mark	

Fitting	
Input Type	Constant Current
IP Rating	IP66
Light Source	LED built in

Gear	
Gear Type	Led Driver
Input Voltage	120-240V
50 Hz	Yes
60 Hz	Yes

IP Rating	IP20
Safety Class	
Dimmable	No

Illumination Data	
Colour Code	2700K-3300K-4000K
Lumen Output	8250lm (75W)
Light Efficiency	110lm/W
CRI	80
Illumination Diagram	

Packing Info	
Box Weight	9.300kg
Pcs/Carton	1
Barcode	5291889080725
HS Code	9405413990

Certification & Warranty	
Warranty	5 years

switch to
one light!

