
Product Datasheet

www.1-light.eu

05 Downlights Fixed>The 3-12W Round Recessed Panels Aluminium

10108FA/W/C



8W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms.

Complete with 300mA non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP40 80 CRI CE


Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	05 Downlights Fixed
Family	The 3-12W Round Recessed Panels Aluminium
Order Code	10108FA/W/C
Colour	White
Material	Die Cast
Diffuser Material	Acrylic
Shape	Circular

Height	22mm
Diameter	120mm
Cutout Hole Diameter	108mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	23V
Safety Class	
Power(Watts)	6,9W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Epistar
LED Number	42

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,2-7,2W
Power Factor	0,6
Constant Current	Yes
Output	300mA
Voltage Range	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	560lm
Light Efficiency	70lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	18,5cm
Box Width	3,1cm
Box Height	13cm
Box Weight	0.242kg
Pcs/Carton	40
Barcode	5291889044055
HS Code	9405119090

Certification & Warranty

Warranty	2 years
Weee Directive	Yes

switch to
one light!

