Product Datasheet

www.1-light.eu

02 Recessed Spots Fixed LED>Floating Ring Range

10112R/W/W



12W Dark Light COB LED recessed spot with interchargeable ring.

Ring must be ordered separately.

Requires 700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



050162/B



050162/DC



050162/W



89015A

Related items



89015AT

Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	Floating Ring Range
Order Code	10112R/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	97mm
Diameter	85mm
Cutout Hole Diameter	68mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Safety Class	III
Power(Watts)	12W
IP Rating	IP65
Light Source	LED built in

LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	1100lm
Light Efficiency	91,67lm/W
CRI	90
Beam Angle	50°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	9cm
Box Width	9cm
Box Height	8,5cm
Box Weight	0.362kg
Pcs/Carton	50
Barcode	5291889074205
HS Code	9405413990

Certification & Warranty

Warranty	5 years

switch to
one light!

