Product Datasheet

www.1-light.eu

04 Recessed Spots Adjustable LED>The Mirror Adjustable Boxes

11107T/W/W



7W Adjustable Dark light recessed spot, IP20.

Complete with 160mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI ADJUSTABLE DARK LIGHT CE

Downloads

IES

Dimensions



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The Mirror Adjustable Boxes
Order Code	11107T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	63mm
Diameter	82mm
Cutout Hole Diameter	74mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes

Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting

Input Type	Constant Current
Input Current	160mA
Voltage	40V
Safety Class	⧫ III
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Osram
LED Number	1
F Mark	▽ F

Gear

Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	4-6,72W
Power Factor	0,5
Constant Current	Yes
Output	160mA
Voltage Range	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C…+50°C
Operating Temp	75°C
Brand	Lifud
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	560lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.280kg
Pcs/Carton	30
Barcode	5291889075356
HS Code	9405413990

Certification & Warranty

Warranty	5 years

switch to
one light!

