Product Datasheet

www.1-light.eu

12 Wall & Ceiling LED>LED Decorative Cylinders

12108T/W/W



8W COB LED adjustable ceiling light.

Complete with black and brass reflectors.

Supplied with 700mA driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI ADJUSTABLE DARK LIGHT CE

Downloads

IES CE

Dimensions



Physical Specification

Item Group	12 Wall & Ceiling LED
Family	LED Decorative Cylinders
Order Code	12108T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	80mm
Diameter	70mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	9V
Safety Class	
Power(Watts)	6,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	3,5-6,3W
Power Factor	0,8
Constant Current	Yes
700mA	5-9V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU
Protection	Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	720lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.340kg
Pcs/Carton	30
Barcode	5291889076490
HS Code	9405413990

Certification & Warranty

Warranty	5 years

switch to
one light!

