# Product Datasheet

www.1-light.eu

10 Office & Kitchen>CCT V Opal Recessed LED Linear Profiles

38152R/W/V



CCT and Power variable 40W recessed linear fitting with diffuser, ideal for offices.

Complete with power variable driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 CCT V PV 90 CRI CE


## Downloads


IES

## Dimensions




## Gallery





## Related items



38152RC/W/V

## Physical Specification

| | |
|---|---|
| Item Group | 10 Office & Kitchen |
| Family | CCT V Opal Recessed LED Linear Profiles |

| | |
|---|---|
| Order Code | 38152R/W/V |
| Colour | White |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 1210mm |
| Width | 70mm |
| Height | 60mm |
| Cutout Hole Width | 60mm |
| Cutout Hole Length | 1200mm |
| Recessed Ceiling | Yes |
| Depth Required | 80mm |
| Indoor | Yes |
| Adjustable | No |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | ⏚ |
| Power(Watts) | 20W-30W-40W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | F |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| IP Rating | IP20 |

| | |
|---|---|
| Light Source | LED built in |
| LED Type | SMD |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| IP Rating | IP20 |
| Dimmable | No |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K-4000K-5000K |
| Lumen Output | 3600lm (40W) |
| Light Efficiency | 90lm/W |
| CRI | 90 |
| Beam Angle | 120° |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Weight | 2.366kg |
| Pcs/Carton | 12 |
| Barcode | 5291889082576 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 3 years |

switch to
one light!

