Product Datasheet

www.1-light.eu

20 Industrial & Floodlights>The Industrial IP65 UFO Range CCT V & PV

63150N/V



CCT Variable and power adjustable 90W/120W/150W SMD LED Industrial High Bay, IP65.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP65 CCT V PV 80 CRI 90° CE

Downloads

IES

Dimensions



Physical Specification

Item Group	20 Industrial & Floodlights
Family	The Industrial IP65 UFO Range CCT V & PV
Order Code	63150N/V
Colour	Black
Material	Aluminium
Diffuser Material	PC
Shape	Circular
Height	169mm
Diameter	310mm
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	90W/120W/150W
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Cable Length	150cm
F Mark	

Fitting

Input Type	Constant Current
Light Source	LED built in
LED Type	SMD 2835

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power Factor	0,9
Constant Current	Yes

Illumination Data

Colour Temperature	4000K-4700K-5700K
Lumen Output	22500lm (150W)
Light Efficiency	150lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Weight	2.800kg
Pcs/Carton	1
Barcode	5291889078357
HS Code	9405413990

Certification & Warranty

Warranty	5 years
Weee Directive	Yes

switch to
one light!

