Product Datasheet

www.1-light.eu

08 Track Lights>The COB Track Light Range Aluminium

65612NT/W/C



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI ADJUSTABLE CE

Downloads

IES

Dimensions



Related items


40001A/W


40002A/W


40003A/W


40003R/W

Physical Specification

Item Group	08 Track Lights
Family	The COB Track Light Range Aluminium
Order Code	65612NT/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	123mm

Diameter	90mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting

Input Type	Constant Current
Input Current	750mA
Voltage	38V
Safety Class	
Power(Watts)	28,5W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear

Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	25-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Protection	Short Circuit Protection

Illumination Data

Colour Temperature	4000K
Lumen Output	2700lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	

Packing Info

Box Length	25cm
Box Width	10cm
Box Height	10cm
Box Weight	1.140kg
Pcs/Carton	10
Barcode	5291889057901

HS Code	9405413990

Certification & Warranty

Warranty	3 years
Weee Directive	Yes

switch to
one light!

