Product Datasheet

www.1-light.eu

12 Wall & Ceiling LED>The Dark Light Cylinders CCT V

12106E/B/V



6W CCT Variable LED surface mounted downlight.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 CCT V 90 CRI DARK LIGHT CE

Downloads

IES

Dimensions



Physical Specification

Item Group	12 Wall & Ceiling LED
Family	The Dark Light Cylinders CCT V
Order Code	12106E/B/V
Colour	Black
Material	Aluminium
Shape	Circular
Height	95mm
Diameter	65mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Light Source	LED built in
LED Type	COB

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Output	150mA
Dimmable	No

Illumination Data

Colour Temperature	3000K-3500K-4000K
Lumen Output	420lm
Light Efficiency	70lm/W

CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.250kg
Pcs/Carton	50
Barcode	5291889084174
HS Code	9405413990

Certification & Warranty

Warranty	3 years

switch to
one light!

